

KEL-DPZ CR multi-membrane cable entry plates, round

for the use in cleanrooms, M25 - M63 / IP66 / IP68 / UL Type 12/4X*



KEL-DPZ CR round cable entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The assembly of the KEL-DPZ CR round with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ CR round provides strain relief and protection IP66 / IP68 / UL Type 4X*.

The round versions of the KEL-DPZ CR series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

The products with article ending .600 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1. The materials used for these products have been tested and certified for outgassing according to VOC/SVOC (ISO 14644-8; ISO 16000-6,-9,-11,-25, VDI 2083 sheet 17).

The products with the article ending .601 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1.

*4X for indoor use only

IP54	IP55	IP64	IP65	IP66	IP67
IP68	UL TYPE 12	UL TYPE 4X*	UL US	DNV	RIFA
HL3 EN 45545-2	EN 61373	ECOLAB certified	UV ISO 4892-2A	EN ISO 14644	PNEUMATICS
RoHS compliant	REACH COMPLIANCE	Made in Germany			

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type (UL 50E)	UL Type 12, UL Type 4X*
Material	Elastomer Base frame: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut

Advantages & benefits

- Fast mounting
- High cable density
- Certified protection IP66/IP68 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Hexagonal locknut included in the delivery
- Hygienic design - free of dirt-collecting recesses

Product types & sizes


KEL-DPZ 25|3 CR gy



Part No.	43736.601
EAN	4251269328268
Package quantity	5
For max. no. of cables	3
Max. cable diameter	6,5 mm
Colour	grey (similar RAL 7035)
Height	22 mm


Mounting height	8 mm
External diameter	39 mm
Cut-out size, round	25,3 mm
Cut-out size, metric	M25
Thread	M25 x 1,5
Thread length	14 mm
(S)VOC tested	No
Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm

KEL-DPZ 25|3 CR
(S)VOC gy




Part No.	43736.600	Mounting height	8 mm
EAN	4251269327964	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	3	Cut-out size, metric	M25
Max. cable diameter	6,5 mm	Thread	M25 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm

KEL-DPZ 25|3 CR bk




Part No.	50736.601	Mounting height	8 mm
EAN	4251269328411	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	3	Cut-out size, metric	M25
Max. cable diameter	6,5 mm	Thread	M25 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm

KEL-DPZ 25|3 CR
(S)VOC bk




Part No.	50736.600	Mounting height	8 mm
EAN	4251269328114	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	3	Cut-out size, metric	M25
Max. cable diameter	6,5 mm	Thread	M25 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm

KEL-DPZ 25|4 CR gy




Part No.	43737.601	Mounting height	8 mm
EAN	4251269328275	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	4	Cut-out size, metric	M25
Max. cable diameter	5,2 mm	Thread	M25 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 3.2 - 5.2 mm

KEL-DPZ 25|4 CR
(S)VOC gy




Part No.	43737.600	Mounting height	8 mm
EAN	4251269327971	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	4	Cut-out size, metric	M25
Max. cable diameter	5,2 mm	Thread	M25 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 5.2 mm




Part No.	50737.601	Mounting height	8 mm
EAN	4251269328428	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	4	Cut-out size, metric	M25
Max. cable diameter	5,2 mm	Thread	M25 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 3.2 - 5.2 mm

KEL-DPZ 25|4 CR
(S)VOC bk




Part No.	50737.600	Mounting height	8 mm
EAN	4251269328121	External diameter	39 mm
Package quantity	5	Cut-out size, round	25,3 mm
For max. no. of cables	4	Cut-out size, metric	M25
Max. cable diameter	5,2 mm	Thread	M25 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 5.2 mm

KEL-DPZ 32|4 CR gy




Part No.	43732.601	Mounting height	8 mm
EAN	4251269328237	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	12,5 mm	Thread	M32 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm

KEL-DPZ 32|4 CR
(S)VOC gy




Part No.	43732.600	Mounting height	8 mm
EAN	4251269327933	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	12,5 mm	Thread	M32 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm

KEL-DPZ 32|4 CR bk




Part No.	50732.601	Mounting height	8 mm
EAN	4251269328381	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	12,5 mm	Thread	M32 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm

KEL-DPZ 32|4 CR
(S)VOC bk




Part No.	50732.600	Mounting height	8 mm
EAN	4251269328084	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	12,5 mm	Thread	M32 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm

KEL-DPZ 32|4-2 CR gy




Part No.	43733.601	Mounting height	8 mm
EAN	4251269328244	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	9,5 mm	Thread	M32 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 5 - 9.5 mm

KEL-DPZ 32|4-2 CR
(S)VOC gy




Part No.	43733.600	Mounting height	8 mm
EAN	4251269327940	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	9,5 mm	Thread	M32 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 5 - 9.5 mm

KEL-DPZ 32|4-2 CR bk




Part No.	50733.601	Mounting height	8 mm
EAN	4251269328398	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	9,5 mm	Thread	M32 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 5 - 9.5 mm


KEL-DPZ 32|4-2 CR
(S)VOC bk




Part No.	50733.600	Mounting height	8 mm
EAN	4251269328091	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	9,5 mm	Thread	M32 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 5 - 9.5 mm

KEL-DPZ 32|7 CR gy


Part No.	43734.601	Mounting height	8 mm
EAN	4251269328251	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	7	Cut-out size, metric	M32
Max. cable diameter	6,5 mm	Thread	M32 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	7 x 3.2 - 6.5 mm

KEL-DPZ 32|7 CR (S)VOC gy


Part No.	43734.600	Mounting height	8 mm
EAN	4251269327957	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	7	Cut-out size, metric	M32
Max. cable diameter	6,5 mm	Thread	M32 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	7 x 3.2 - 6.5 mm

KEL-DPZ 32|7 CR bk

Part No.	50734.601	Mounting height	8 mm
EAN	4251269328404	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	7	Cut-out size, metric	M32
Max. cable diameter	6,5 mm	Thread	M32 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	7 x 3.2 - 6.5 mm


KEL-DPZ 32|7 CR (S)VOC bk

Part No.	50734.600	Mounting height	8 mm
EAN	4251269328107	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	7	Cut-out size, metric	M32
Max. cable diameter	6,5 mm	Thread	M32 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	7 x 3.2 - 6.5 mm

KEL-DPZ 40|8 CR gy

Part No.	43741.601	Mounting height	8 mm
EAN	4251269328282	External diameter	52 mm
Package quantity	5	Cut-out size, round	40,4 mm
For max. no. of cables	8	Cut-out size, metric	M40
Max. cable diameter	10,2 mm	Thread	M40 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm

KEL-DPZ 40|8 CR
(S)VOC gy




Part No. **43741.600**
EAN **4251269327988**
Package quantity **5**
For max. no. of cables **8**
Max. cable diameter **10,2 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
ja
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm

KEL-DPZ 40|8 CR bk




Part No. **50741.601**
EAN **4251269328435**
Package quantity **5**
For max. no. of cables **8**
Max. cable diameter **10,2 mm**
Colour **black**
Height **22 mm**

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
No
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm

KEL-DPZ 40|8 CR
(S)VOC bk




Part No. **50741.600**
EAN **4251269328138**
Package quantity **5**
For max. no. of cables **8**
Max. cable diameter **10,2 mm**
Colour **black**
Height **22 mm**

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
ja
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm

KEL-DPZ 50|8 CR gy




Part No. **43750.601**
EAN **4251269328299**
Package quantity **5**
For max. no. of cables **8**
Max. cable diameter **12,5 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
No
5 x 5 - 10.2 mm
3 x 7.2 - 12.5 mm

KEL-DPZ 50|8 CR
(S)VOC gy




Part No. **43750.600**
EAN **4251269327995**
Package quantity **5**
For max. no. of cables **8**
Max. cable diameter **12,5 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range


8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
ja
5 x 5 - 10.2 mm
3 x 7.2 - 12.5 mm

KEL-DPZ 50|8 CR bk




Part No.	50750.601	Mounting height	8 mm
EAN	4251269328442	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	8	Cut-out size, metric	M50
Max. cable diameter	12,5 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm

KEL-DPZ 50|8 CR (S)VOC bk




Part No.	50750.600	Mounting height	8 mm
EAN	4251269328145	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	8	Cut-out size, metric	M50
Max. cable diameter	12,5 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm

KEL-DPZ 50|10 CR CR gy




Part No.	43751.601	Mounting height	8 mm
EAN	4251269328305	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	10	Cut-out size, metric	M50
Max. cable diameter	22,2 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm

KEL-DPZ 50|10 CR (S)VOC gy




Part No.	43751.600	Mounting height	8 mm
EAN	4251269328008	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	10	Cut-out size, metric	M50
Max. cable diameter	22,2 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm

KEL-DPZ 50|10 CR bk




Part No.	50751.601	Mounting height	8 mm
EAN	4251269328459	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	10	Cut-out size, metric	M50
Max. cable diameter	22,2 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm

KEL-DPZ 50|10 CR
(S)VOC bk




Part No.	50751.600	Mounting height	8 mm
EAN	4251269328152	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	10	Cut-out size, metric	M50
Max. cable diameter	22,2 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm

KEL-DPZ 50|12 CR gy




Part No.	43752.601	Mounting height	8 mm
EAN	4251269328312	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	12	Cut-out size, metric	M50
Max. cable diameter	10,2 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm

KEL-DPZ 50|12 CR
(S)VOC gy




Part No.	43752.600	Mounting height	8 mm
EAN	4251269328015	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	12	Cut-out size, metric	M50
Max. cable diameter	10,2 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm

KEL-DPZ 50|12 CR bk




Part No.	50752.601	Mounting height	8 mm
EAN	4251269328466	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	12	Cut-out size, metric	M50
Max. cable diameter	10,2 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	4 x 3.2 - 6.5 mm


KEL-DPZ 50|12 CR
(S)VOC bk




Part No.	50752.600	Mounting height	8 mm
EAN	4251269328169	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	12	Cut-out size, metric	M50
Max. cable diameter	10,2 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR gy


Part No.	43758.601	Mounting height	8 mm
EAN	4251269328336	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	19 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR (S)VOC gy


Part No.	43758.600	Mounting height	8 mm
EAN	4251269328039	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	19 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR bk

Part No.	50758.601	Mounting height	8 mm
EAN	4251269328480	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	19 x 3.2 - 6.5 mm


KEL-DPZ 50|19 CR (S)VOC bk

Part No.	50758.600	Mounting height	8 mm
EAN	4251269328183	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	19 x 3.2 - 6.5 mm

KEL-DPZ 50|78 CR gy

Part No.	43756.601	Mounting height	8 mm
EAN	4251269328329	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	78	Cut-out size, metric	M50
Max. cable diameter	5 mm	Thread	M50 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	76 x 1.5 - 2.6 mm 2 x 2.5 - 5 mm


KEL-DPZ 50|78 CR
(S)VOC gy



Part No. **43756.600**
EAN **4251269328022**
Package quantity **5**
For max. no. of cables **78**
Max. cable diameter **5 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm


KEL-DPZ 50|78 CR
(S)VOC bk



Part No. **50756.600**
EAN **4251269328176**
Package quantity **5**
For max. no. of cables **78**
Max. cable diameter **5 mm**
Colour **black**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm


KEL-DPZ 50|78 CR bk



Part No. **50756.601**
EAN **4251269328473**
Package quantity **5**
For max. no. of cables **78**
Max. cable diameter **5 mm**
Colour **black**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **No**
Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm


KEL-DPZ 63|9 CR gy



Part No. **43760.601**
EAN **4251269328343**
Package quantity **5**
For max. no. of cables **9**
Max. cable diameter **22,2 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**


Mounting height
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **No**
Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm

KEL-DPZ 63|9 CR
(S)VOC gy



Part No. **43760.600**
EAN **4251269328046**
Package quantity **5**
For max. no. of cables **9**
Max. cable diameter **22,2 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|9 CR bk

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Colour
Height

50760.601
4251269328497
5
9
22,2 mm
black
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
No
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|9 CR (S)VOC bk

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Colour
Height

50760.600
4251269328190
5
9
22,2 mm
black
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
ja
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|13 CR gy

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Colour
Height

43761.601
4251269328350
5
13
16,2 mm
grey (similar RAL 7035)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
No
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm


KEL-DPZ 63|13 CR (S)VOC gy

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Colour
Height

43761.600
4251269328053
5
13
16,2 mm
grey (similar RAL 7035)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
ja
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

KEL-DPZ 63|13 CR bk


Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Colour
Height

50761.601
4251269328503
5
13
16,2 mm
black
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range


8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
No
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

**KEL-DPZ 63|13 CR
(S)VOC bk**




Part No.	50761.600	Mounting height	8 mm
EAN	4251269328206	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	13	Cut-out size, metric	M63
Max. cable diameter	16,2 mm	Thread	M63 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm
			4 x 5 - 10.2 mm
			5 x 9 - 16.2 mm

KEL-DPZ 63|14 CR gy




Part No.	43762.601	Mounting height	8 mm
EAN	4251269328367	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Thread	M63 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	14 x 5 - 10.2 mm

**KEL-DPZ 63|14 CR
(S)VOC gy**




Part No.	43762.600	Mounting height	8 mm
EAN	4251269328060	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Thread	M63 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	14 x 5 - 10.2 mm

KEL-DPZ 63|14 CR bk




Part No.	50762.601	Mounting height	8 mm
EAN	4251269328510	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Thread	M63 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	14 x 5 - 10.2 mm

**KEL-DPZ 63|14 CR
(S)VOC bk**




Part No.	50762.600	Mounting height	8 mm
EAN	4251269328213	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Thread	M63 × 1,5
Colour	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	14 x 5 - 10.2 mm

KEL-DPZ 63|35 CR gy



Part No.	43763.601	Mounting height	8 mm
EAN	4251269328374	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	35	Cut-out size, metric	M63
Max. cable diameter	6,5 mm	Thread	M63 × 1,5
Colour	grey (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	No
		Clamping range	35 x 3.2 - 6.5 mm


KEL-DPZ 63|35 CR
(S)VOC gy



Part No. **43763.600**
EAN **4251269328060**
Package quantity **5**
For max. no. of cables **35**
Max. cable diameter **6,5 mm**
Colour **grey (similar RAL 7035)**
Height **22 mm**

Mounting height **8 mm**
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **35 x 3.2 - 6.5 mm**


KEL-DPZ 63|35 CR bk



Part No. **50763.601**
EAN **4251269328527**
Package quantity **5**
For max. no. of cables **35**
Max. cable diameter **6,5 mm**
Colour **black**
Height **22 mm**

Mounting height **8 mm**
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **No**
Clamping range **35 x 3.2 - 6.5 mm**

KEL-DPZ 63|35 CR
(S)VOC bk



Part No. **50763.600**
EAN **4251269328220**
Package quantity **5**
For max. no. of cables **35**
Max. cable diameter **6,5 mm**
Colour **black**
Height **22 mm**

Mounting height **8 mm**
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **35 x 3.2 - 6.5 mm**