


KEL-DPZ-CLICK | Multi-membrane cable entry plates

for snap-in mounting, M25 - M63 / IP65 / IP66 / IP68



KEL-DPZ-CLICK cable entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The new variant of the proven cable entry plate KEL-DPZ is snapped into the cut-out directly from the front. This significantly reduces the assembly time. Alternatively, the new variant can be fastened with a locknut. The KEL-DPZ-CLICK series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

Snapped into the cut-out:

For wall thickness 1 – 2.5 mm
Protection IP65

Fixed with a locknut:

For max. wall thickness 11 mm
Protection IP66 / IP68

The assembly of the KEL-DPZ-CLICK with unterminated cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-CLICK provides strain relief and protection IP65 / IP66 / IP68 (certified acc. to EN 60529).

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Locknuts are NOT included in the shipment.

IP54

IP68

IP55

Made in Germany

IP64

RoHS compliant

IP65

IP66

IP67

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Material	Elastomer Base frame: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut,Snap-in

Advantages & benefits

- Fast mounting
- Offers two mounting types: Snap-in and locknut fixation
- High cable density
- Certified protection classes IP65/IP66/IP68 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Hygienic design - free of dirt-collecting recesses







Product types & sizes






KEL-DPZ-CLICK 25|3
9y




Part No.	44050
EAN	4251269323065
Package quantity	10
For max. no. of cables	3
Max. cable diameter	6,5 mm
Colour	grey (similar RAL 7035)
Height	28 mm

Mounting height	8 mm
External diameter	39 mm
Cut-out size, round	25,3 mm
Cut-out size, metric	M25
Thread	M25 x 1,5
Thread length	20 mm
Suitable locknut	52284
Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm

KEL-DPZ-CLICK 25 4 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44051 4251269323072 10 4 5,2 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 20 mm 52284 4 x 3.2 - 5.2 mm
KEL-DPZ-CLICK 32 4 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44052 4251269323089 10 4 12,5 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 20 mm 52285 3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm
KEL-DPZ-CLICK 32 4-2 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44053 4251269323096 10 4 9,5 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 20 mm 52285 4 x 5 - 9.5 mm
KEL-DPZ-CLICK 32 7 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44054 4251269323102 10 7 6,5 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 20 mm 52285 7 x 3.2 - 6.5 mm
KEL-DPZ-CLICK 40 8 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44055 4251269323119 10 8 10,2 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 52 mm 40,4 mm M40 M40 × 1,5 20 mm 52286 4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm
KEL-DPZ-CLICK 50 8 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44056 4251269323126 10 8 12,5 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 20 mm 52287 5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm


KEL-DPZ-CLICK 50 10 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44057 4251269323133 10 10 22,2 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 20 mm 52287 7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm
KEL-DPZ-CLICK 50 12 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44058 4251269323140 10 12 10,2 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 20 mm 52287 4 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm
KEL-DPZ-CLICK 50 19 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44059 4251269323157 10 19 6,5 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 20 mm 52287 19 x 3.2 - 6.5 mm
KEL-DPZ-CLICK 50 78 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44060 4251269323164 10 78 5 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 20 mm 52287 76 x 1.5 - 2.6 mm 2 x 2.5 - 5 mm
KEL-DPZ-CLICK 63 9 gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Colour Height	44061 4251269323171 10 9 22,2 mm grey (similar RAL 7035) 28 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Suitable locknut Clamping range	8 mm 75 mm 63,4 mm M63 M63 × 1,5 20 mm 52288 1 x 3.2 - 6.5 mm 3 x 5 - 10.2 mm 4 x 9 - 16.2 mm 1 x 16 - 22.2 mm



Part No. **44062**
EAN **4251269323188**
Package quantity **10**
For max. no. of cables **13**
Max. cable diameter **16,2 mm**
Colour **grey (similar RAL 7035)**
Height **28 mm**

Mounting height **8 mm**
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **20 mm**
Suitable locknut **52288**
Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm


KEL-DPZ-CLICK 63|14
gy



Part No. **44063**
EAN **4251269323195**
Package quantity **10**
For max. no. of cables **14**
Max. cable diameter **10,2 mm**
Colour **grey (similar RAL 7035)**
Height **28 mm**

Mounting height **8 mm**
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **20 mm**
Suitable locknut **52288**
Clamping range **14 x 5 - 10.2 mm**

KEL-DPZ-CLICK 63|35
gy



Part No. **44064**
EAN **4251269323201**
Package quantity **10**
For max. no. of cables **35**
Max. cable diameter **6,5 mm**
Colour **grey (similar RAL 7035)**
Height **28 mm**

Mounting height **8 mm**
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **20 mm**
Suitable locknut **52288**
Clamping range **35 x 3.2 - 6.5 mm**