


QVT-CLICK | Split cable gland for snap-in mounting

for cables with connectors, M16 - M50 / IP54



QVT-CLICK is a circular split frame for quick and easy installation of pre-terminated cables or complete cable harnesses. But also electric, pneumatic or hydraulic lines without terminals or connectors as well as corrugated conduits can be easily routed and sealed with IP54. Because of its extremely compact design, the QVT-CLICK range is especially suitable for small machines, devices and instruments.

The cable glands are easy to install. The prefabricated cable is placed into the slit grommet which is set into one of the gland halves. Depending on the size of the cable gland, one, two or four separate grommets can be installed. By using multi-hole grommets up to 16 lines can be routed with one cable gland.

The QVT-CLICK can be assembled without tools from the front side of the enclosure wall. Sizes QVT-CLICK 16, QVT-CLICK 20, QVT-CLICK 40|1 and QVT-CLICK 50 can be also screwed with a [locknut](#).

A sealing ring is included in the shipment.

Note:

Snap-in assembly QVT-CLICK 16 + 20 (wall thickness 1.5 - 2.5 mm)
Snap-in assembly QVT-CLICK 25 + 32 + 40 + 50 (wall thickness 1 - 2.5 mm)

IP54

HL3
EN 45545-2

ECOLAB
certified

Made in
Germany

RoHS
compliant

REACH
COMPLIANCE

Specifications


IP rating (EN 60529)	IP54
Material	Polycarbonate
Flame class	UL94-V0, self-extinguishing
Operating temperature	-30 C° to 100 C°
Mounting options	Snap-in

Advantages & benefits

- Fast and easy mounting from the front side
- Space-saving shape
- Routing of cables with and without connectors
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Fast mounting by snapping into the cut-out
- Greatly increased cable density when using double or quadruple grommets

Product types & sizes


QVT-CLICK 16 gy



Part No.	45726
EAN	4251269320552
Package quantity	10
For max. no. of cables	1
Max. cable diameter	10 mm
Colour	grey (similar RAL 7035)
External diameter	32 mm


Mounting height	13,5 mm
Cut-out size, metric	M16
Cut-out size, round	16,2 mm
Thread	M16 x 1,5
Thread length	13 mm
For min. wall thickness	1,5 mm
For max. wall thickness	2,5 mm
Suitable locknut	52272, 31105
Suitable for grommets	1 x QT small

QVT-CLICK 20 gy




Part No.	45728	Cut-out size, metric	M20
EAN	4251269320569	Cut-out size, round	20,4 mm
Package quantity	10	Thread	M20 × 1,5
For max. no. of cables	2	Thread length	13 mm
Max. cable diameter	11 mm	For min. wall thickness	1,5 mm
Height	27,8 mm	For max. wall thickness	2,5 mm
Mounting height	13,5 mm	Suitable locknut	52273, 31110
		Suitable for grommets	1 x QT small

QVT-CLICK 25 gy




Part No.	45730	Mounting height	13,5 mm
EAN	4251269311529	Cut-out size, metric	M25
Package quantity	10	Cut-out size, round	25,5 mm
For max. no. of cables	4	For min. wall thickness	1 mm
Max. cable diameter	15 mm	For max. wall thickness	2,5 mm
Colour	grey (similar RAL 7035)	Suitable for grommets	1 x QT small
External diameter	39 mm		

QVT-CLICK 32 gy




Part No.	45732	Mounting height	13,5 mm
EAN	4251269311536	Cut-out size, metric	M32
Package quantity	10	Cut-out size, round	32,5 mm
For max. no. of cables	4	For min. wall thickness	1 mm
Max. cable diameter	15 mm	For max. wall thickness	2,5 mm
Colour	grey (similar RAL 7035)	Suitable for grommets	1 x QT small
External diameter	39 mm		

QVT-CLICK 40-1 gy




Part No.	45736	Mounting height	13,5 mm
EAN	4251269323973	Cut-out size, metric	M40
Package quantity	10	Cut-out size, round	40,5 mm
For max. no. of cables	1	Thread	M40 × 1,5
Max. cable diameter	29 mm	Thread length	20 mm
Colour	grey (similar RAL 7035)	For min. wall thickness	1 mm
External diameter	50 mm	For max. wall thickness	2,5 mm
		Suitable locknut	52276, 45107, 31130
		Suitable for grommets	1 x QT large

QVT-CLICK 40-2 gy




Part No.	45734	Mounting height	13,5 mm
EAN	4251269311543	Cut-out size, metric	M40
Package quantity	10	Cut-out size, round	40,5 mm
For max. no. of cables	8	For min. wall thickness	1 mm
Max. cable diameter	15 mm	For max. wall thickness	2,5 mm
Colour	grey (similar RAL 7035)	Suitable for grommets	2 x QT small
External diameter	50 mm		

QVT-CLICK 50-1 gy



Part No.	45738	Mounting height	22 mm
EAN	4251269323980	Cut-out size, metric	M50
Package quantity	10	Cut-out size, round	50,4 mm
For max. no. of cables	1	Thread	M50 × 1,5
Max. cable diameter	29 mm	Thread length	20 mm
Colour	grey (similar RAL 7035)	For min. wall thickness	1 mm
External diameter	62 mm	For max. wall thickness	2,5 mm
		Suitable locknut	52277, 45108, 31140
		Suitable for grommets	1 x QT large

QVT-CLICK 50-4 gy



Part No.

EAN

Package quantity

For max. no. of cables

Max. cable diameter

Colour

External diameter

45740

4251269323997

10

16

15 mm

grey (similar RAL 7035)

62 mm

Mounting height

Cut-out size, metric

Cut-out size, round

Thread

Thread length

For min. wall thickness

For max. wall thickness

Suitable locknut

Suitable for grommets

22 mm

M50

50,4 mm

M50 × 1,5

20 mm

1 mm

2,5 mm

52277, 45108, 31140

4 x QT small

icotek[®]
smart cable management