

KDRS-BES-U | Split base plates with brush strips

for Rittal VX25 enclosures



The 2-piece enclosure base plates are supplied with preassembled brush strips.

The gland plates are installed with standard Rittal screws.

Depending on the maximum cable diameter to be routed, the 2 halves of the brush base plate are aligned further or closer to each other.

The base plates are perfect for protection of the enclosure interior against dirt.

Specifications

Material	Base plate: Steel, zinc plated Brushes: Polyamide
Operating temperature	-20 C° to 90 C°
Properties	silicone free, halogen free


Advantages & benefits

- During assembly, almost the complete base of the enclosure can be used for installation of cables
- Subsequent assembly possible

Product types & sizes

KDRS-BES-U-VX25-1000 (50mm) 	Part No.	58032	Division bar	Yes
	EAN	4251269328923	Brush height	50 mm
	Package quantity	1	For wall thickness	2,5 - 3 mm
	Length	438 mm	Suitable for enclosure	Rittal VX25
	Width	16 mm		
	For enclosure width	1.000 mm		
	Sight size of base opening	402 mm		
KDRS-BES-U-VX25-1200 (50mm) 	Part No.	58033	Division bar	Yes
	EAN	4251269328930	Brush height	50 mm
	Package quantity	1	For wall thickness	2,5 - 3 mm
	Length	538 mm	Suitable for enclosure	Rittal VX25
	Width	16 mm		
	For enclosure width	1.200 mm		
	Sight size of base opening	502 mm		

KDRS-BES-U-VX25-600
(50mm)



Part No.	58030
EAN	4251269328909
Package quantity	1
Length	488 mm
Width	16 mm
For enclosure width	600 mm
Sight size of base opening	452 mm

Brush height	50 mm
For wall thickness	2,5 - 3 mm
Suitable for enclosure	Rittal VX25

KDRS-BES-U-VX25-800
(50mm)



Part No.	58031
EAN	4251269328916
Package quantity	1
Length	688 mm
Width	16 mm
For enclosure width	800 mm
Sight size of base opening	652 mm

Brush height	50 mm
For wall thickness	2,5 - 3 mm
Suitable for enclosure	Rittal VX25