

ALLIO

Compact LED lighting for industry and IT applications



With its compact design and 190° rotating tube, the ALLIO system luminaire offers space-saving lighting for enclosures. This also enables easy retrofitting in existing enclosures.

The High Power LED illuminates with 1050 lumens and offers a service life of 50,000 hours. The opal white polycarbonate tube provides a homogeneous, glare-free area light.

A [door operated switch](#) is available as an option.

IP20

Made in Germany

CE

UKCA

IK07

IK08

RoHS compliant

REACH COMPLIANCE


Specifications


IP rating (EN 60529)	IP20
Protection class	II (Protective insulation)
Material	Tube: Polycarbonate Enclosure: Polycarbonate
Flame class	
Operating temperature	-20 C° to 50 C°
Mounting options	Screw type mounting,Magnetic attachment,Clip attachment (patented)

Advantages & Benefits


- Compact design with 190° rotating LED tube
- Various mounting types: with magnets, screw assembly or snap-in assembly in the 19" server rack
- Easy retrofitting in existing enclosures
- Effective LED lighting with 1050 lumens
- Available with motion sensor
- Door operated switch available as an option

Product Types & Sizes







Part No.	81100	Length	3.000 mm
EAN	4251269333019	connecting cable	
Package quantity	1	Version	Standard
UL Certificate	-	Connection possibilities	Door operated switch
Length	448 mm	Connector type	Ferrules
Height	56,5 mm	Rated power	8 W
Width	26,2 mm	Operating voltage	24 V DC
		Test standard	EN 60598, EN 55015, EN 61000, EN 62741
		Guidelines	2014/35/EU, 2014/30/EU
		Service life	50.000 h
		Energy efficiency class	E
		Color temperature	5.600 K
		Color rendering index CRI	> 80
		Luminous flux W	1.000 lm
		Color	gray (similar RAL 7035)




Part No.	81101	Length	3.000 mm
EAN	4251269333026	connecting cable	
Package quantity	1	Version	PIR motion detector
UL Certificate	-	Connector type	Ferrules
Length	448 mm	Rated power	8 W
Height	56,5 mm	Operating voltage	24 V DC
Width	26,2 mm	Test standard	EN 60598, EN 55015, EN 61000, EN 62741
		Guidelines	2014/35/EU, 2014/30/EU
		Service life	50.000 h
		Energy efficiency class	E
		Color temperature	5.600 K
		Color rendering index CRI	> 80
		Luminous flux W	1.000 lm
		Color	gray (similar RAL 7035)




Part No.	81102	Length	3.000 mm
EAN	4251269333033	connecting cable	
Package quantity	1	Version	Standard
UL Certificate	-	Connection possibilities	Door operated switch
Length	448 mm		Ferrules
Height	56,5 mm	Connector type	
Width	26,2 mm	Rated power	8 W
		Operating voltage	220 - 240 V AC, 50 - 60 Hz
		Test standard	EN 60598, EN 55015, EN 61000, EN 62741
		Guidelines	2014/35/EU, 2014/30/EU
		Service life	50.000 h
		Energy efficiency class	E
		Color temperature	5.600 K
		Color rendering index CRI	> 80
		Luminous flux W	1.000 lm
		Color	gray (similar RAL 7035)



Part No.	81103	Length	1.500 mm
EAN	4251269333040	connecting cable	
Package quantity	1	Version	Standard
UL Certificate	-	Connection possibilities	Door operated switch
Length	448 mm	Connector type	Plug CEE 7/17
Height	56,5 mm	Rated power	8 W
Width	26,2 mm	Operating voltage	220 - 240 V AC, 50 - 60 Hz
		Test standard	EN 60598, EN 55015, EN 61000, EN 62741
		Guidelines	2014/35/EU, 2014/30/EU
		Service life	50.000 h
		Energy efficiency class	E
		Color	5.600 K
		temperature	
		Color rendering index CRI	> 80
		Luminous flux W	1.000 lm
		Color	gray (similar RAL 7035)



Part No.	81104	Length	3.000 mm
EAN	4251269333057	connecting cable	
Package quantity	1	Version	Standard
UL Certificate	-	Connection possibilities	Door operated switch
Length	448 mm	Connector type	Ferrules
Height	56,5 mm	Rated power	8 W
Width	26,2 mm	Operating voltage	100 - 240 V AC, 50 - 60 Hz
		Test standard	EN 60598, EN 55015, EN 61000, EN 62741
		Guidelines	2014/35/EU, 2014/30/EU
		Service life	50.000 h
		Energy efficiency class	E
		Color temperature	5.600 K
		Color rendering index CRI	> 80
		Luminous flux W	1.000 lm
		Color	gray (similar RAL 7035)



Part No.	81105	Length	3.000 mm
EAN	4251269333064	connecting cable	
Package quantity	1	Version	PIR motion detector
UL Certificate	-	Connector type	Ferrules
Length	448 mm	Rated power	8 W
Height	56,5 mm	Operating voltage	100 - 240 V AC, 50 - 60 Hz
Width	26,2 mm	Test standard	EN 60598, EN 55015, EN 61000, EN 62741
		Guidelines	2014/35/EU, 2014/30/EU
		Service life	50.000 h
		Energy efficiency class	E
		Color temperature	5.600 K
		Color rendering index CRI	> 80
		Luminous flux W	1.000 lm
		Color	gray (similar RAL 7035)

Faceplate for 19" rack bk



Part No.	81135	No. of screw	4
EAN	4251269333101	holes	
Package quantity	1	Diam. of screw	6,5 mm
Length	484 mm	holes	
Height	6 mm		
Width	44 mm		
Color	black		

**Faceplate for 19" rack
gy**



Part No. **81134**
EAN **4251269333095**
Package quantity **1**
Length **484 mm**
Height **6 mm**
Width **44 mm**
Color **gray (similar RAL 7035)**

No. of screw holes **4**
Diam. of screw holes **6,5 mm**

icotek[®]
smart cable management