


KEL-DP | Multi-membrane cable entry plates

pluggable, with high cable density / IP64 / UL Type 12



KEL-DP entry plates are designed for routing cables without connectors, hoses or fibre optics in limited space.

The KEL-DP products are an easy to assemble and cost saving alternative to traditional cable glands. Simply make a small hole in the thin membrane and push the cables through. The KEL-DP provides protection IP64 / UL type 12.

The KEL-DP matches exactly the cut-out dimensions of 6-, 10-, 16- and 24-pin standard industrial connectors. The very compact size KEL-DP-E is designed for routing cables in very small space. Through a cut-out of only 18 × 112 mm, up to 21 cables can be easily routed and sealed. A special rib ensures a centred fit in the cut-outs.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

IP54

HL3
EN 45545-2

REACH
COMPLIANCE

IP64

UL TYPE
12

ECOLAB
certified

Made in
Germany

RoHS
compliant

Specifications

IP rating (EN 60529)	IP54, IP64
UL Type (UL 50E)	UL Type 12
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-30 C° to 100 C°
Properties	halogen free, silicone free
Mounting options	Snap-in


Advantages & Benefits

- Quick assembly without tools
- High cable density
- Cost-effective solution
- Hygienic design - free of dirt-collecting recesses

Product Types & Sizes

KEL-DP 24 12 A bk	Part No.	50508	Width	44 mm
	EAN	4251269314612	Height	12
	Package quantity	10	Mounting height	5 mm
	For max. no. of cables	12	Cut-out size	112 × 36 mm
	Max. cable diameter	15 mm	For min. wall thickness	1,5 mm
	Color	black	For max. wall thickness	2,5 mm
	Length	142 mm	For wall thickness	1,5 - 2,5 mm
			Clamping range	12 x 1 - 15 mm

KEL-DP 24|12 A gy




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Length

43508
4251269309830
10
12
15 mm
gray (similar RAL 7035)
142 mm

Width
Height
Mounting height
Cut-out size
For min. wall thickness
For max. wall thickness
For wall thickness
Clamping range

44 mm
12
5 mm
112 × 36 mm
1,5 mm
2,5 mm
1,5 - 2,5 mm
12 x 1 - 15 mm

KEL-DP 24|12 B bk



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Length

50510
4251269334634
10
12
15 mm
black
142 mm

Width
Height
Mounting height
Cut-out size
For min. wall thickness
For max. wall thickness
For wall thickness
Clamping range

44 mm
12
5 mm
112 × 36 mm
2,8 mm
4 mm
2,8 - 4 mm
12 x 1 - 15 mm

KEL-DP 24|12 B gy



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Length

43510
4251269334627
10
12
15 mm
gray (similar RAL 7035)
142 mm

Width
Height
Mounting height
Cut-out size
For min. wall thickness
For max. wall thickness
For wall thickness
Clamping range

44 mm
12
5 mm
112 × 36 mm
2,8 mm
4 mm
2,8 - 4 mm
12 x 1 - 15 mm

KEL-DP 24|14 A bk




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Length

50512
4251269314636
10
14
12,1 mm
black
142 mm

Width
Height
Mounting height
Cut-out size
For min. wall thickness
For max. wall thickness
For wall thickness
Clamping range

44 mm
12
5 mm
112 × 36 mm
1,5 mm
2,5 mm
1,5 - 2,5 mm
14 x 1 - 12.1 mm

KEL-DP 24|14 A gy



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Length

43512
4251269309854
10
14
12,1 mm
gray (similar RAL 7035)
142 mm

Width
Height
Mounting height
Cut-out size
For min. wall thickness
For max. wall thickness
For wall thickness
Clamping range

44 mm
12
5 mm
112 × 36 mm
1,5 mm
2,5 mm
1,5 - 2,5 mm
14 x 1 - 12.1 mm

KEL-DP 24|14 B bk




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Length

50522
4251269314711
10
14
12,1 mm
black
142 mm

Width
Height
Mounting height
Cut-out size
For min. wall thickness
For max. wall thickness
For wall thickness
Clamping range

44 mm
12
5 mm
112 × 36 mm
2,8 mm
4 mm
2,8 - 4 mm
14 x 1 - 12.1 mm

KEL-DP 24|14 B gy




Part No.	43522	Width	44 mm
EAN	4251269309939	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	14	Cut-out size	112 × 36 mm
Max. cable diameter	12,1 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	14 x 1 - 12.1 mm

KEL-DP 24|17 A bk



Part No.	50514	Width	44 mm
EAN	4251269314643	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	12,6 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	5 x 1 - 10.5 mm 12 x 1 - 12.6 mm

KEL-DP 24|17 A gy




Part No.	43514	Width	44 mm
EAN	4251269309861	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	12,6 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	5 x 1 - 10.5 mm 12 x 1 - 12.6 mm

KEL-DP 24|17 B bk




Part No.	50523	Width	44 mm
EAN	4251269314728	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	12,6 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	5 x 1 - 10.5 mm 12 x 1 - 12.6 mm

KEL-DP 24|17 B gy



Part No.	43523	Width	44 mm
EAN	4251269309946	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	12,6 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	5 x 1 - 10.5 mm 12 x 1 - 12.6 mm

KEL-DP 24|18 A bk



Part No.	50515	Width	44 mm
EAN	4251269314650	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	18	Cut-out size	112 × 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	4 x 1 - 6.5 mm
			5 x 1 - 10.5 mm
			5 x 1 - 12.6 mm
			4 x 1 - 16.1 mm

KEL-DP 24|18 A gy




Part No.	43515	Width	44 mm
EAN	4251269309878	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	18	Cut-out size	112 × 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	4 x 1 - 6.5 mm
			5 x 1 - 10.5 mm
			5 x 1 - 12.6 mm
			4 x 1 - 16.1 mm

KEL-DP 24|18 B bk




Part No.	50528	Width	44 mm
EAN	4251269314773	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	18	Cut-out size	112 × 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	4 x 1 - 6.5 mm
			5 x 1 - 10.5 mm
			5 x 1 - 12.6 mm
			4 x 1 - 16.1 mm

KEL-DP 24|18 B gy




Part No.	43528	Width	44 mm
EAN	4251269309991	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	18	Cut-out size	112 × 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	4 x 1 - 6.5 mm
			5 x 1 - 10.5 mm
			5 x 1 - 12.6 mm
			4 x 1 - 16.1 mm

KEL-DP 24|19 A bk




Part No.	50516	Width	44 mm
EAN	4251269314667	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	19	Cut-out size	112 × 36 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	12 x 1 - 6.5 mm
			7 x 1 - 12.1 mm

KEL-DP 24|19 A gy




Part No.	43516	Width	44 mm
EAN	4251269309885	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	19	Cut-out size	112 × 36 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	12 x 1 - 6.5 mm
			7 x 1 - 12.1 mm

KEL-DP 24|19 B bk



Part No.	50524	Width	44 mm
EAN	4251269314735	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	19	Cut-out size	112 × 36 mm
Max. cable diameter	12,1 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	12 x 1 - 6.5 mm
			7 x 1 - 12.1 mm

KEL-DP 24|19 B gy



Part No.	43524	Width	44 mm
EAN	4251269309953	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	19	Cut-out size	112 × 36 mm
Max. cable diameter	12,1 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	12 x 1 - 6.5 mm
			7 x 1 - 12.1 mm

KEL-DP 24|26 A bk



Part No.	50518	Width	44 mm
EAN	4251269314674	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	26	Cut-out size	112 × 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	16 x 1 - 6.5 mm
			4 x 1 - 12.1 mm
			4 x 1 - 16.1 mm

KEL-DP 24|26 A gy



Part No.	43518	Width	44 mm
EAN	4251269309892	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	26	Cut-out size	112 x 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	16 x 1 - 6.5 mm
			4 x 1 - 12.1 mm
			4 x 1 - 16.1 mm

KEL-DP 24|26 B bk



Part No.	50525	Width	44 mm
EAN	4251269314742	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	26	Cut-out size	112 x 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	16 x 1 - 6.5 mm
			4 x 1 - 12.1 mm
			4 x 1 - 16.1 mm

KEL-DP 24|26 B gy




Part No.	43525	Width	44 mm
EAN	4251269309960	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	26	Cut-out size	112 x 36 mm
Max. cable diameter	16,1 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	16 x 1 - 6.5 mm
			4 x 1 - 12.1 mm
			4 x 1 - 16.1 mm

KEL-DP 24|42 A bk



Part No.	50511	Width	44 mm
EAN	4251269314629	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	42	Cut-out size	112 x 36 mm
Max. cable diameter	4,7 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	12 x 1 - 7.2 mm
			17 x 1 - 6.4 mm
			12 x 1 - 5 mm
			1 x 1 - 4.7 mm

KEL-DP 24|42 A gy




Part No.	43511	Width	44 mm
EAN	4251269309847	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	42	Cut-out size	112 x 36 mm
Max. cable diameter	4,7 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	12 x 1 - 7.2 mm
			17 x 1 - 6.4 mm
			12 x 1 - 5 mm
			1 x 1 - 4.7 mm

KEL-DP 24|42 B bk



Part No.	50521	Width	44 mm
EAN	4251269314704	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	42	Cut-out size	112 × 36 mm
Max. cable diameter	4,7 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	12 x 1 - 7.2 mm
			17 x 1 - 6.4 mm
			12 x 1 - 5 mm
			1 x 1 - 4.7 mm

KEL-DP 24|42 B gy




Part No.	43521	Width	44 mm
EAN	4251269309922	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	42	Cut-out size	112 × 36 mm
Max. cable diameter	4,7 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	12 x 1 - 7.2 mm
			17 x 1 - 6.4 mm
			12 x 1 - 5 mm
			1 x 1 - 4.7 mm

KEL-DP 24|48 A bk



Part No.	50519	Width	44 mm
EAN	4251269314681	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	48	Cut-out size	112 × 36 mm
Max. cable diameter	6,5 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	48 x 1 - 6.5 mm

KEL-DP 24|48 A gy




Part No.	43519	Width	44 mm
EAN	4251269309908	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	48	Cut-out size	112 × 36 mm
Max. cable diameter	6,5 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	48 x 1 - 6.5 mm

KEL-DP 24|48 B bk




Part No.	50526	Width	44 mm
EAN	4251269314759	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	48	Cut-out size	112 × 36 mm
Max. cable diameter	6,5 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	48 x 1 - 6.5 mm

KEL-DP 24|48 B gy




Part No.	43526	Width	44 mm
EAN	4251269309977	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	48	Cut-out size	112 × 36 mm
Max. cable diameter	6,5 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	48 x 1 - 6.5 mm

KEL-DP 24|50 A bk




Part No.	50520	Width	44 mm
EAN	4251269314698	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	50	Cut-out size	112 × 36 mm
Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	33 x 1 - 5.3 mm
			9 x 1 - 6.4 mm
			8 x 1 - 8.3 mm

KEL-DP 24|50 A gy




Part No.	43520	Width	44 mm
EAN	4251269309915	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	50	Cut-out size	112 × 36 mm
Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	33 x 1 - 5.3 mm
			9 x 1 - 6.4 mm
			8 x 1 - 8.3 mm

KEL-DP 24|50 B bk








Part No.	50527	Width	44 mm
EAN	4251269314766	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	50	Cut-out size	112 × 36 mm
Max. cable diameter	8,3 mm	For min. wall thickness	2,8 mm
Color	black	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	33 x 1 - 5.3 mm
			9 x 1 - 6.4 mm
			8 x 1 - 8.3 mm


KEL-DP 24|50 B gy



Part No.	43527	Width	44 mm
EAN	4251269309984	Height	12
Package quantity	10	Mounting height	5 mm
For max. no. of cables	50	Cut-out size	112 × 36 mm
Max. cable diameter	8,3 mm	For min. wall thickness	2,8 mm
Color	gray (similar RAL 7035)	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Clamping range	33 x 1 - 5.3 mm
			9 x 1 - 6.4 mm
			8 x 1 - 8.3 mm

KEL-DP 16 10 A gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Length	43460 4251269320750 10 10 12,2 mm gray (similar RAL 7035) 96 mm	Width Height Mounting height Cut-out size For min. wall thickness For max. wall thickness For wall thickness Clamping range	44 mm 12 mm 5 mm 86 × 36 mm 1,5 mm 2,5 mm 1,5 - 2,5 mm 10 x 1 - 12.2 mm
KEL-DP 16 11 A gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Length	43461 4251269320767 10 11 12,6 mm gray (similar RAL 7035) 96 mm	Width Height Mounting height Cut-out size For min. wall thickness For max. wall thickness For wall thickness Clamping range	44 mm 12 mm 5 mm 86 × 36 mm 1,5 mm 2,5 mm 1,5 - 2,5 mm 3 x 1 - 10.5 mm 8 x 1 - 12.6 mm
KEL-DP 16 20 A gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Length	43462 4251269320774 10 20 8,3 mm gray (similar RAL 7035) 96 mm	Width Height Mounting height Cut-out size For min. wall thickness For max. wall thickness For wall thickness Clamping range	44 mm 12 mm 5 mm 86 × 36 mm 1,5 mm 2,5 mm 1,5 - 2,5 mm 20 x 1 - 8.3 mm
KEL-DP 16 22 A gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Length	43463 4251269320781 10 22 6,5 mm gray (similar RAL 7035) 96 mm	Width Height Mounting height Cut-out size For min. wall thickness For max. wall thickness For wall thickness Clamping range	44 mm 12 mm 5 mm 86 × 36 mm 1,5 mm 2,5 mm 1,5 - 2,5 mm 5 x 1 - 12.1 mm 4 x 1 - 8.3 mm 13 x 1 - 6.5 mm
KEL-DP 16 23 A gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Length	43464 4251269320798 10 23 12,1 mm gray (similar RAL 7035) 96 mm	Width Height Mounting height Cut-out size For min. wall thickness For max. wall thickness For wall thickness Clamping range	44 mm 12 mm 5 mm 86 × 36 mm 1,5 mm 2,5 mm 1,5 - 2,5 mm 18 x 1 - 6.5 mm 5 x 1 - 12.1 mm
KEL-DP 16 26 A gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Length	43465 4251269320804 10 26 8,3 mm gray (similar RAL 7035) 96 mm	Width Height Mounting height Cut-out size For min. wall thickness For max. wall thickness For wall thickness Clamping range	44 mm 12 mm 5 mm 86 × 36 mm 1,5 mm 2,5 mm 1,5 - 2,5 mm 19 x 1 - 6.5 mm 7 x 1 - 8.3 mm


KEL-DP 10|8 A gy



Part No. **43466**
EAN **4251269324000**
Package quantity **10**
For max. no. of cables **8**
Max. cable diameter **12,6 mm**
Color **gray (similar RAL 7035)**
Length **75 mm**

Width **44 mm**
Height **12 mm**
Mounting height **5 mm**
Cut-out size **65 × 36 mm**
For min. wall thickness **1,5 mm**
For max. wall thickness **2,5 mm**
For wall thickness **1,5 - 2,5 mm**
Clamping range **8 x 1 - 12.6 mm**


KEL-DP 10|12 A gy



Part No. **43467**
EAN **4251269324017**
Package quantity **10**
For max. no. of cables **12**
Max. cable diameter **12,6 mm**
Color **gray (similar RAL 7035)**
Length **75 mm**

Width **44 mm**
Height **12 mm**
Mounting height **5 mm**
Cut-out size **65 × 36 mm**
For min. wall thickness **1,5 mm**
For max. wall thickness **2,5 mm**
For wall thickness **1,5 - 2,5 mm**
Clamping range **4 x 1 - 6.5 mm**
4 x 1 - 8.3 mm
4 x 1 - 12.6 mm


KEL-DP 10|14 A gy



Part No. **43468**
EAN **4251269324024**
Package quantity **10**
For max. no. of cables **14**
Max. cable diameter **8,3 mm**
Color **gray (similar RAL 7035)**
Length **75 mm**

Width **44 mm**
Height **12 mm**
Mounting height **5 mm**
Cut-out size **65 × 36 mm**
For min. wall thickness **1,5 mm**
For max. wall thickness **2,5 mm**
For wall thickness **1,5 - 2,5 mm**
Clamping range **14 x 1 - 8.3 mm**


KEL-DP 10|16 A gy



Part No. **43469**
EAN **4251269324031**
Package quantity **10**
For max. no. of cables **16**
Max. cable diameter **12,6 mm**
Color **gray (similar RAL 7035)**
Length **75 mm**

Width **44 mm**
Height **12 mm**
Mounting height **5 mm**
Cut-out size **65 × 36 mm**
For min. wall thickness **1,5 mm**
For max. wall thickness **2,5 mm**
For wall thickness **1,5 - 2,5 mm**
Clamping range **12 x 1 - 6.5 mm**
4 x 1 - 12.6 mm


KEL-DP 10|26 A gy



Part No. **43470**
EAN **4251269324048**
Package quantity **10**
For max. no. of cables **26**
Max. cable diameter **6,5 mm**
Color **gray (similar RAL 7035)**
Length **75 mm**


Width **44 mm**
Height **12 mm**
Mounting height **5 mm**
Cut-out size **65 × 36 mm**
For min. wall thickness **1,5 mm**
For max. wall thickness **2,5 mm**
For wall thickness **1,5 - 2,5 mm**
Clamping range **26 x 1 - 6.5 mm**


KEL-DP 6|6 A gy




Part No. **43450**
EAN **4251269320712**
Package quantity **10**
For max. no. of cables **6**
Max. cable diameter **12,1 mm**
Color **gray (similar RAL 7035)**
Length **62 mm**

Width **44 mm**
Height **12 mm**
Mounting height **5 mm**
Cut-out size **52 × 36 mm**
For min. wall thickness **1,5 mm**
For max. wall thickness **2,5 mm**
For wall thickness **1,5 - 2,5 mm**
Clamping range **6 x 1 - 12.1 mm**

KEL-DP 6 12 A gy 	Part No.	43451	Width	44 mm
	EAN	4251269320729	Height	12 mm
	Package quantity	10	Mounting height	5 mm
	For max. no. of cables	12	Cut-out size	52 × 36 mm
	Max. cable diameter	16,1 mm	For min. wall thickness	1,5 mm
	Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
	Length	62 mm	For wall thickness	1,5 - 2,5 mm
			Clamping range	8 x 1 - 6.5 mm 2 x 1 - 12.6 mm 2 x 1 - 16.1 mm


KEL-DP 6 14 A gy 	Part No.	43452	Width	44 mm
	EAN	4251269320736	Height	12 mm
	Package quantity	10	Mounting height	5 mm
	For max. no. of cables	14	Cut-out size	52 × 36 mm
	Max. cable diameter	10,5 mm	For min. wall thickness	1,5 mm
	Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
	Length	62 mm	For wall thickness	1,5 - 2,5 mm
			Clamping range	10 x 1 - 6.5 mm 4 x 1 - 10.5 mm

KEL-DP 6 25 A gy 	Part No.	43453	Width	44 mm
	EAN	4251269320743	Height	12 mm
	Package quantity	10	Mounting height	5 mm
	For max. no. of cables	25	Cut-out size	52 × 36 mm
	Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
	Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
	Length	62 mm	For wall thickness	1,5 - 2,5 mm
			Clamping range	21 x 1 - 5 mm 4 x 1 - 8.3 mm

KEL-DP-E 46 7 gy 	Part No.	43585	Width	25 mm
	EAN	4251269310287	Height	12 mm
	Package quantity	10	Mounting height	5 mm
	For max. no. of cables	7	Cut-out size	46 × 18 mm
	Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
	Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
	Length	62 mm	For wall thickness	1,5 - 2,5 mm
			Clamping range	5 x 1 - 8.3 mm 2 x 1 - 6.5 mm

KEL-DP-E 46 7 bk 	Part No.	50585	Width	25 mm
	EAN	4251269315008	Height	12 mm
	Package quantity	10	Mounting height	5 mm
	For max. no. of cables	7	Cut-out size	46 × 18 mm
	Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
	Color	black	For max. wall thickness	2,5 mm
	Length	62 mm	For wall thickness	1,5 - 2,5 mm
			Clamping range	5 x 1 - 8.3 mm 2 x 1 - 6.5 mm

KEL-DP-E 46|9 gy



Part No.	43587	Width	25 mm
EAN	4251269310294	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	9	Cut-out size	46 × 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	62 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	8 x 1 - 6.5 mm
			1 x 1 - 12.1 mm

KEL-DP-E 46|9 bk



Part No.	50587	Width	25 mm
EAN	4251269315015	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	9	Cut-out size	46 × 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	62 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	8 x 1 - 6.5 mm
			1 x 1 - 12.1 mm

KEL-DP-E 86|13 gy



Part No.	43581	Width	25 mm
EAN	4251269310263	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	13	Cut-out size	85 × 18 mm
Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	102 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	11 x 1 - 8.3 mm
			2 x 1 - 6.5 mm

KEL-DP-E 86|13 bk



Part No.	50581	Width	25 mm
EAN	4251269314988	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	13	Cut-out size	85 × 18 mm
Max. cable diameter	8,3 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	102 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	11 x 1 - 8.3 mm
			2 x 1 - 6.5 mm

KEL-DP-E 86|17 gy




Part No.	43583	Width	25 mm
EAN	4251269310270	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	17	Cut-out size	85 × 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	102 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	16 x 1 - 6.5 mm
			1 x 1 - 12.1 mm

KEL-DP-E 86|17 bk



Part No.	50583	Width	25 mm
EAN	4251269314995	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	17	For min. wall thickness	1,5 mm
Max. cable diameter	12,1 mm	For max. wall thickness	2,5 mm
Color	black	For wall thickness	1,5 - 2,5 mm
Length	102 mm	Clamping range	16 x 1 - 6.5 mm 1 x 1 - 12.1 mm

KEL-DP-E 112|16 gy



Part No.	43576	Width	25 mm
EAN	4251269310249	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	16	Cut-out size	112 x 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	128 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	4 x 1 - 6.5 mm 11 x 1 - 8.3 mm 1 x 1 - 12.1 mm

KEL-DP-E 112|16 bk



Part No.	50576	Width	25 mm
EAN	4251269314964	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	16	Cut-out size	112 x 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	128 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	4 x 1 - 6.5 mm 11 x 1 - 8.3 mm 1 x 1 - 12.1 mm

KEL-DP-E 112|21 gy



Part No.	43578	Width	25 mm
EAN	4251269310256	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	21	Cut-out size	112 x 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	128 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	16 x 1 - 6.5 mm 4 x 1 - 8.3 mm 1 x 1 - 12.1 mm

KEL-DP-E 112|21 bk



Part No.	50578	Width	25 mm
EAN	4251269314971	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	21	Cut-out size	112 x 18 mm
Max. cable diameter	12,1 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	128 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	16 x 1 - 6.5 mm 4 x 1 - 8.3 mm 1 x 1 - 12.1 mm

KEL-DP-S 69|8 gy



Part No.	43591	Width	19,5 mm
EAN	4251269310300	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	8	Cut-out size	69 × 10 mm
Max. cable diameter	7,5 mm	For min. wall thickness	1,5 mm
Color	gray (similar RAL 7035)	For max. wall thickness	2,5 mm
Length	78 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	8 x 1 - 7.5 mm

KEL-DP-S 69|8 bk



Part No.	50591	Width	19,5 mm
EAN	4251269315022	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	8	Cut-out size	69 × 10 mm
Max. cable diameter	7,5 mm	For min. wall thickness	1,5 mm
Color	black	For max. wall thickness	2,5 mm
Length	78 mm	For wall thickness	1,5 - 2,5 mm
		Clamping range	8 x 1 - 7.5 mm