

□□□ □□, M32 - M63 / IP66 / IP68, FDA □□



IP54	IP55	IP64	IP65	IP66	IP67	IP68
Made in Germany	FDA	1935/ 2004/ EG	EU VO. 10/2011	ECOLAB certified	 EN ISO 14644	 PNEUMATICS
RoHS compliant	 REACH COMPLIANCE	 UL US				

IP	IP54, IP55, IP64, IP65, IP66, IP67, IP68
EN 60529	
	-40 C° to 80 C°

□□□□ KEL-DPZ-HD CR□ M32 - M63 □□□ □□□□ □□□□□, □□가□ □ □□ □□□□ □□□□□□□□.

[illegible]

이 제품은 최대 두께가 3.2mm로 22.2mm 이하의 모든 스마트폰과 호환됩니다. IP65/66/67/68 등급 방수 기능을 갖춘 이 제품은 수영장에서 사용할 수 있습니다. 또한 야외에서 사용하기에 적합하며, 내열 및 내충격 성능을 갖추고 있습니다.


이 제품이 .600mm 두께의 ISO14644-1에 따라 1등급의 청정도를 갖는 청정실에서 제조되었습니다. 이 제품은 또한 VOC/ISO 16000-6,-9,-11,-25, VDI 2083 sheet 17)에 따라 테스트된 청정 제품입니다.

본사가 .601을 통해 ISO14644-1을 통해 100%의 공기 청정도를 달성할 수 있다.

□ □ □ □

- 1935/2004/EG, (EU) 10/2011
- FDA
- 식품의약품안전처 (EHEDG)
- Ecolab
- 식품 안전
- 식품 안전
- 식품 안전
- 식품 안전 3.2mm 22mm
- 식품 안전 및 식품 안전
- 식품 안전 및 식품 안전
- 식품 안전 (IP66/68)
- 식품 안전
- 식품 안전
- 식품 안전
- 식품, 음료, 식품, 식품 안전
- 식품 안전
- 식품 안전

□ □ □ □ □ □ □



EAN

□□□ □
□□ □□□ □□


70351.601
4251269328657
5
4
12,5 mm
□□(RAL 5005 □ □□)
22 mm

00 00
 00 000
 00 00 000
 0000 00 000

000 00
 00 000 (ISO 4287)
 (S)VOC tested
 000 00 0

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 µm

3 x 3.2 - 6.5 mm
1 x 7.2 - 12.5 mm



EAN


□□□ □
□□ □□□ □□

70351.600
4251269328534
5
4
12,5 mm
□□(RAL 5005 □ □□)
22 mm

□□ □□
□□ □□□
□□ □□ □□□
□□□□ □□ □□□

000 00
 00 000 (ISO 4287)
 (S)VOC tested
 000 00 0

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 μm
ja
3 x 3.2 - 6.5 mm
1 x 7.2 - 12.5 mm



EAN

0000 0
00 0000 00


70352.601
4251269328664
5
4
9,5 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 μm

4 x 5 - 9.5 mm



EAN


0000 0
00 0000 00

70352.600
4251269328541
5
4
9,5 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 μm
ja
4 x 5 - 9.5 mm



EAN

0000 0
00 0000 00


70353.601
4251269328671
5
7
6,5 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 μm

7 x 3.2 - 6.5 mm



EAN


0000 0
00 0000 00

70353.600
4251269328558
5
7
6,5 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 μm
ja
7 x 3.2 - 6.5 mm



EAN

0000 0
00 0000 00


70354.601
4251269328688
5
8
10,2 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
Ra = 0,421 μm

4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm



EAN


0000 0
00 0000 00

70354.600
4251269328565
5
8
10,2 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
Ra = 0,421 μm
ja
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm



EAN

0000 0
00 0000 00


70355.601
4251269328695
5
8
12,5 mm
00(RAL 5005 00)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 μm

5 x 5 - 10.2 mm
3 x 7.2 - 12.5 mm




EAN
0000 0
00 0000 00

70355.600
4251269328572
5
8
12,5 mm
00(RAL 5005 0 00)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm
ja
5 x 5 - 10.2 mm
3 x 7.2 - 12.5 mm



EAN
0000 0
00 0000 00


70356.601
4251269328701
5
10
22,2 mm
00(RAL 5005 0 00)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm

7 x 3.2 - 6.5 mm
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm




EAN
0000 0
00 0000 00

70356.600
4251269328589
5
10
22,2 mm
00(RAL 5005 0 00)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm
ja
7 x 3.2 - 6.5 mm
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm



EAN
0000 0
00 0000 00


70357.601
4251269328718
5
12
10,2 mm
00(RAL 5005 0 00)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm

4 x 3.2 - 6.5 mm
8 x 5 - 10.2 mm




EAN
0000 0
00 0000 00

70357.600
4251269328596
5
12
10,2 mm
00(RAL 5005 0 00)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm
ja
4 x 3.2 - 6.5 mm
8 x 5 - 10.2 mm



EAN
0000 0
00 0000 00


70358.601
4251269328725
5
19
6,5 mm
00(RAL 5005 0 00)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm

19 x 3.2 - 6.5 mm



EAN


0000 0
00 0000 00

70358.600
4251269328602
5
19
6,5 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
62 mm
50,4 mm
M50
M50 x 1,5
14 mm
Ra = 0,421 µm
ja
19 x 3.2 - 6.5 mm



EAN

0000 0
00 0000 00


70359.601
4251269328732
5
9
22,2 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 x 1,5
14 mm
Ra = 0,421 µm

1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm



EAN


0000 0
00 0000 00

70359.600
4251269328619
5
9
22,2 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 x 1,5
14 mm
Ra = 0,421 µm
ja
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm



EAN

0000 0
00 0000 00


70360.601
4251269328749
5
13
16,2 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 x 1,5
14 mm
Ra = 0,421 µm

4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm



EAN


0000 0
00 0000 00

70360.600
4251269328626
5
13
16,2 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 x 1,5
14 mm
Ra = 0,421 µm
ja
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm



EAN

0000 0
00 0000 00


70361.601
4251269328756
5
14
10,2 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 0000
00 00 0000
0000 00 0000

0000 00
00 0000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 x 1,5
14 mm
Ra = 0,421 µm

14 x 5 - 10.2 mm




EAN
0000 0
00 0000 00

70361.600
4251269328633
5
14
10,2 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm
ja
14 x 5 - 10.2 mm



EAN
0000 0
00 0000 00


70362.601
4251269328763
5
35
6,5 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm

35 x 3.2 - 6.5 mm



EAN
0000 0
00 0000 00

70362.600
4251269328640
5
35
6,5 mm
RAL 5005 (RAL 5005 000)
22 mm

00 00
00 000
00 00 000
0000 00 000

0000 00
00 000 (ISO 4287)
(S)VOC tested
0000 00 0

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm
ja
35 x 3.2 - 6.5 mm