

KEL-ERM VARIO |

, 가 / IP65 / UL Type 12/4X*



KEL-ERM VARIO .

, 가 . , .

KEL-ERM VARIO , .

1~16 mm(KT1~KT15) 16~35 mm(KT16~KT34) , IP65 UL Type 12/4X* EN 62444 .

KEL-ER 가, , .

KEL-ERM VARIO 10, 16, 24 (heavy duty) . KEL-ERM VARIO B 46 × 46 mm (,) .

, IP65 .

KEL-ERM VARIO ()가 , , .

, '' . .

*4X

IP (EN 60529) IP54, IP55, IP64, IP65
UL Type (UL 50E) UL Type 12, UL Type 4X*

UL94-V0,
-40 C° to 140 C°
, UV-, , (V2A),

- 가 (: 24|10, 24|7, 24|4)
-
-
- 가
- , 가
- EN 62444
-
-
- IMAS-CONNECT 가™

-
- 68341
 - EAN 4251269337901
 - 10
 - 10
 - 35 mm
 - 147 mm
 - 65 mm
-
- 22 mm
 - 22 mm
 - 112 × 36 mm
 - 4
 - 5,8 mm
 -

-
- 68341.200
 - EAN 4251269337949
 - 10
 - 10
 - 35 mm
 - 147 mm
 - 65 mm
-
- 22 mm
 - 22 mm
 - 112 × 36 mm
 - 4
 - 5,8 mm
 - (V2A)

-
- 68342
 - EAN 4251269337918
 - 10
 - 8
 - 35 mm
 - 120 mm
 - 65 mm
-
- 22 mm
 - 22 mm
 - 86 × 36 mm
 - 4
 - 5,8 mm
 -



- 68342.200
- EAN 4251269337956
- 10
- 8
- 35 mm
- 120 mm
- 65 mm

- 22 mm
- 22 mm
- 86 × 36 mm
- 4
- 5,8 mm
- (V2A)



- 68343
- EAN 4251269337925
- 10
- 6
- 35 mm
- 98 mm
- 65 mm

- 22 mm
- 22 mm
- 65 × 36 mm
- 4
- 5,8 mm
-



- 68343.200
- EAN 4251269337963
- 10
- 6
- 35 mm
- 98 mm
- 65 mm

- 22 mm
- 22 mm
- 65 × 36 mm
- 4
- 5,8 mm
- (V2A)



- 68344
- EAN 4251269337932
- 10
- 4
- 35 mm
- 73 mm
- 65 mm

- 22 mm
- 22 mm
- 46 × 46 mm
- 4
- 5,8 mm
-



- 68344.200
- EAN 4251269337970
- 10
- 4
- 35 mm
- 73 mm
- 65 mm

- 22 mm
- 22 mm
- 46 × 46 mm
- 4
- 5,8 mm
- (V2A)

KEL-ERM-VARIO



- 68345
- EAN 4251269338069
- 10

