

KEL-JUMBO flex | 100000 100000 1000 1000 1000

100000 100 100 68 mm 100 100 70 / IP54 / IP68 / UL Type 12



KEL-JUMBO flex 100 27-68mm 100 100 70 1000 1000 1000 1000.

100 100000 10000 1000 1000 100000.

1000000 1070 1000 100 100000.

KEL-JUMBO flex 10000 100 1000 10000 **25%** 100 100 100000. 10000 1000 10000 10000.

IP54

ECOLAB
certified

UL TYPE
12

ISO 4892-2A

C_{RU}US

RoHS
compliant

RIFA

REACH
COMPLIANCE

HL3
EN 45545-2

Made in
Germany

EN 61373

100 100 100

- 1000 10000 10000 100 100 100

1000 10000 (88 × 88 mm)

IP 10000 (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
	100000 1000 100000
	UL94-V0, 100000
	-40 C° to 100 C°
	100000, 1000 100
100 100	100 1000

100 100 100 100

	EAN	42614 4251269309021	88 mm
		1	62 mm
	1000 100	1	62 mm
	100 1000 100	48 mm	57,6 mm
		100(RAL 7035 1000)	4
		88 mm	6,9 mm
			27 - 48 mm
			1 x 27 - 48 mm

	EAN	42616 4251269309038	88 mm
		1	62 mm
	1000 100	1	62 mm
	100 1000 100	68 mm	75,5 mm
		100(RAL 7035 1000)	4
		88 mm	6,9 mm
			47 - 68 mm
			1 x 47 - 68 mm

