


□□ □□ 65 mm □□가□ / IP54 / UL Type 12





□□ □□ (Cut-out) □ □□□□. □□ □□ (Cut-out) □□□ □□ □□□ □□□ +15 ~ 20%□□□.


IP 等級 (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
	密封構造
	UL94-V0, 無燄
	-40 C° to 140 C°
	AC, UV-照射, 耐油 試験, 耐電圧(V2A 鋼), 耐腐蝕
耐 熱	耐 熱
耐 寒	35 mm

☐ ☐ ☐ ☐ ☐

- 65mm의 길이
- 10mm의 폭
- 10mm의 두께
- EN 62444 규격 준수



	EAN □□□ □ □□ □□□ □□	42360 4251269308550 1 1 65 mm 110 mm 116 mm	□□ □□ □□ □□□ □□ □ □□ □□□ □□ □□□ □□ □□□□ □□	35 mm 35 mm 78 × 80.5 mm 4 7 mm □□□□ □ 1 x KTF
	EAN □□□ □ □□ □□□ □□	42360.200 4251269308567 1 1 65 mm 110 mm 116 mm	□□ □□ □□ □□□ □□ □ □□ □□□ □□ □□□ □□ □□□□ □□	35 mm 35 mm 78 × 80.5 mm 4 7 mm □□□□□□ (V2A) 1 x KTF




EAN
0000 0
00 000 00

42350
4251269308536
1
2
65 mm
200 mm
116 mm

00 00
00 000
00 0 0
000 00
000 00
0000 00

35 mm
35 mm
168 × 80.5 mm
4
7 mm
00000 0
2 x KTF



EAN
0000 0
00 000 00

42350.200
4251269308543
1
2
65 mm
200 mm
116 mm

00 00
00 000
00 0 0
000 00
000 00
0000 00

35 mm
35 mm
168 × 80.5 mm
4
7 mm
000000 (V2A)
2 x KTF