

KT-DT | 4x1 - 14.5 mm / IP54 / UL Type 12



IP54

E45
Ei30
EN 45545-3

Made in
Germany

UL TYPE
12

ECOLAB
certified

CULUS

UV
ISO 4892-2A

DNV

PNEUMATICS

RIFA

RoHS
compliant

HL3
EN 45545-2

REACH
COMPLIANCE

KT-DT 4x1는 4x1 - 14.5 mm (4x1 - 14.5 mm)의 크기입니다. 이 제품은 4x1 - 14.5 mm의 크기로 제공됩니다.


KT-DT 1 - KT-DT 5 4x1 - 14.5 mm의 크기로 제공됩니다, KT-DT 7 - KT-DT 8 4x1 - 14.5 mm의 크기로 제공됩니다.

4x1 - 14.5 mm의 크기로 제공됩니다.

IP 4x1 (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
	4x1 - 14.5 mm
	UL94-V0, 4x1 - 14.5 mm
	-40 C° to 100 C°
	4x1 - 14.5 mm, 4x1 - 14.5 mm

- 4x1 - 14.5 mm
- 4x1 - 14.5 mm의 크기로 제공됩니다.
 - 4x1 - 14.5 mm의 크기로 제공됩니다.
 - 4x1 - 14.5 mm의 크기로 제공됩니다.

4x1 - 14.5 mm




EAN
4251269319204

41550
4251269319204
10
4
RAL 7035 (RAL 7035)
21 mm
21 mm

4x1 - 14.5 mm
4x1 - 14.5 mm
4x1 - 14.5 mm
4x1 - 14.5 mm

19 mm
2 mm
4x1 - 6 mm
4 x 1 - 6 mm




EAN
□□□ □

41552
4251269319211
10
4
□□(RAL 7035□ □)
21 mm
21 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

19 mm
2 mm
□□ □□□
2× 1 - 4 mm | 2× 1 - 7 mm
2 x 1 - 7 mm
2 x 1 - 4 mm




EAN
□□□ □

41500
4251269307287
10
14
□□(RAL 7035□ □)
41,5 mm
40,5 mm

□□ □□
□□□ □□
□□□ □□ □

□□□ □□ □

19 mm
2 mm
□□ □□□
12× 1 - 6,5 mm | 12× 1 - 12,2 mm
12 x 1 - 6.5 mm
2 x 1 - 12.2 mm




EAN
□□□ □

41510
4251269307294
10
16
□□(RAL 7035□ □)
41,5 mm
40,5 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

19 mm
2 mm
□□ □□□
16× 1 - 7,1 mm
16 x 1 - 7.1 mm




EAN
□□□ □

41520
4251269307300
10
10
□□(RAL 7035□ □)
41,5 mm
40,5 mm

□□ □□
□□□ □□
□□□ □□ □

□□□ □□ □

19 mm
2 mm
□□ □□□
4× 1 - 6,5 mm | 3× 1 - 9,5 mm
| 3× 1 - 11,3 mm
4 x 1 - 6.5 mm
3 x 1 - 9.5 mm
3 x 1 - 11.3 mm




EAN
□□□ □

41530
4251269307317
10
9
□□(RAL 7035□ □)
41,5 mm
40,5 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

19 mm
2 mm
□□ □□□
9× 1 - 9,5 mm
9 x 1 - 9.5 mm



EAN
□□□ □

41540
4251269319099
10
5
□□(RAL 7035□ □)
41,5 mm
40,5 mm

□□ □□
□□□ □□
□□□ □□ □

□□□ □□ □

19 mm
2 mm
□□ □□□
1× 1 - 9,5 mm | 4× 1 - 14,5 mm
mm
4 x 1 - 14.5 mm
1 x 1 - 9.5 mm

