

KTMB 183 | 34 - 75 mm (KEL 183)

34 - 75 mm / IP54 / UL Type 12



IP54

ECOLAB certified

UL TYPE 12

ISO 4892-2A

CULUS

RoHS compliant

RIWA

REACH COMPLIANCE

HL3 EN 45545-2


Made in Germany

EN 61373

75 mm KTMB KEL 183 KTMB , , .
KTMB-O . (10 mm),

IP (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
	UL94-V0,
	-40 C° to 100 C°
	,


- 75mm
- 10 mm



EAN

41410
4251269307133
1
(RAL 7035)
91 mm
86 mm
19 mm


2 mm
1



EAN

41415
4251269307140
1
1
(RAL 7035)
91 mm
86 mm

19 mm
2 mm
 34 - 44 mm
1 x 34 - 44 mm




EAN

□□□ □

41420
4251269307157
1
1
□□(RAL 7035□ □□)
91 mm
86 mm

□□ □□
□□□ □□ □
□□□ □□ □

19 mm
2 mm
44 - 54 mm
1 x 44 - 54 mm




EAN

□□□ □

41425
4251269307164
1
1
□□(RAL 7035□ □□)
91 mm
86 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

19 mm
2 mm
□□ □□□
54 - 64 mm
1 x 54 - 64 mm



EAN

□□□ □

41430
4251269307171
1
1
□□(RAL 7035□ □□)
91 mm
86 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

19 mm
2 mm
□□ □□□
64 - 75 mm
1 x 64 - 75 mm