

Connectorbehuizingen & insertsets 3A / 4A

voor adaptertules AT-HA & kabelinvoerframes MIS



icotek offers 3A or 4A insert sets and matching connector housings with integrated M20 (cable diam. 6 - 12 mm) or M25 (cable diam. 13 - 18 mm) cable glands for [adapter grommets AT-HA](#) and [split cable entry frames MIS](#).

The connector housings are compatible and CE-compliant with numerous insert manufacturers (Harting, Ilme, Phoenix Contact, TE Connectivity, Weidmüller, Lapp, Amphenol, Molex, RS Pro, ...).


EN 45545-2


certified


ISO 4892-2A




IK04


IEC 61984


UL 1977


UL ECBT2


RoHS compliant


COMPLIANCE


Made in Germany


UL

Specificaties

Materiaal	Behuizing: Polyamide Einsatz: Polycarbonaat
Vlam klasse	UL94-V0, zelfdovend
Temperatuur	-40 C° tot 125 C°
Eigenschappen	zonder siliconen, halogeenvrij

Voordelen

Producttypes en maten



Art.nr.

EAN

Aantal

Nominale stroom

Nominale spanning

55510

4251269337499

5

10 A

230 V



Art.nr.	55511
EAN	4251269337
	529
Aantal	5
Nominale stroom	10 A
Nominale spanning	230 V



Art.nr.	55514
EAN	
Aantal	5
Cable gland	M20
Voor	1 x 6 - 12
kabeldiameter	mm
s	



Art.nr.	55515
EAN	
Aantal	5
Cable gland	M25
Voor	1 x 13 - 18
kabeldiameter	mm
s	

