

**IP65****ECOLAB**
certified**IP64****RoHS**
compliant**IP55****REACH**
COMPLIANCE**IP54****UL**
USMade in
Germany**HL3**
EN 45545-2**ccnederland** [Bestel direct online @ CC Nederland »](#)**Electro-flandria** [Voor aanvragen uit België klik hier »](#)

The new bulkhead KEL-FW is perfect for routing cables with/without connectors at a 90° angle over a large bending radius (max. 150 mm).

The hinged cover of the new bulkhead KEL-FW is firmly connected to the housing by a hinge and is therefore captive. This makes the system very easy and quick to mount. The KEL-FW is first screwed to the enclosure using the two rear holes and then fitted with the required cable grommets. The cover is then folded down, locked in place and screwed to the enclosure using the two front holes.

The KEL-FW is fitted with an integrated seal to achieve the high protection rating of IP65 (when using single hole grommets). An additional flat gasket for wall mounting is included in the shipment.


Cables with and without connectors up to a diameter of 35 mm can be routed and strain-relieved according to EN 62444. Retrofitting and maintenance can be carried out quickly and easily.

Specificaties

IP-classificatie (EN 60529)	IP65, IP64, IP55, IP54
Materiaal	Polyamide
Vlam klasse	UL94-V0, zelfdovend
Temperatuur	-40 C° tot 90 C°
Eigenschappen	zonder siliconen, halogeenvrij
Montage type	Schroefbevestiging

Voordelen

Producttypes en maten




Art.nr.
EAN
Aantal
Voor aantal kabels
Max. kabeldiameter
Lengte
Breedte

42460
4251269332074
1
1
35 mm
122 mm
100 mm

Hoogte
Montage hoogte
Aantal schroefgaten
Diameter van schroefgaten
Geschikt voor tules

75 mm
75 mm
4
6,5 mm
1 x KT groot



Art.nr.
EAN
Aantal
Voor aantal kabels
Max. kabeldiameter
Lengte
Breedte

42461
4251269332081
1
4
16 mm
122 mm
100 mm

Hoogte
Montage hoogte
Aantal schroefgaten
Diameter van schroefgaten
Geschikt voor tules

75 mm
75 mm
4
6,5 mm
4 x KT klein

